




## FormTrap Repaginator

- ▶ Overview
- ▶ Loading a Sample Data File
- + Entry
- + Tools
- ▶ Running Repaginator from Command Line

### Running Repaginator from a Command Line



The parameters for Repaginator are as below. The program may be run from a command line prompt or as a filter from the FormTrap Spooler (any version).

```
C:\WINDOWS\system32\cmd.exe
C:\Program Files\TCGIS\FTSpooler>ftrpg /?
ftrpg
FormTrap Repaginator, version 2.1.2
Copyright (c) 2004-2007 ICG Information Systems Pty. Ltd. All rights reserved
No rule file specified, use -rFileName option
Usage: ftrpg [-u] -rRuleFileName [-iinputFileName] [-oOutputFileName] [-lLogFileName]
C:\Program Files\TCGIS\FTSpooler>
```

When running ftrpg from command line you should provide full paths. However if you are running ftrpg as a filter in FTSpooler V7 you can use the two special environment variables:

- %fthome% - location of the home directory
- %ftinst% - location of the installation directory.

The command line in this case would look like this:

```
"%ftinst% ftrpg.exe" -r"%fthome%\Repagination Rules\payment_initial.rpg" -i"%1" -o"%2"
```

Or in case when standard handles are used just:

```
"%ftinst%ftprg.exe" -r" %fthome%\Repagination  
Rules\payment_initial.rpg"
```

This form is preferable because it allows FTSpooler to capture error messages and store them in logs.

The optional `-u` parameter is used only on UNIX platforms when one or more file names contain non-ascii characters. In this case the command line itself should be UTF-8 (Unicode) encoded.

[Top](#)

[Disclaimer](#) | [Home](#) | [About Us](#) | [News](#)  
[Solutions](#) | [Customer Area](#) | [Free Trial](#) | [Success Stories](#) | [Contact Us](#)

**Copyright © 1995 - 2009 TCG Information Systems Pty. Ltd. All rights reserved.**